


Repair Compounds - Cement Based





Manufacturer	Product	Description	Pack Size	Yield
	Mapegrout T40	Medium strength (40 MPa) thixotropic mortar for the repair of concrete. Repairs up to 30-35 mm thick.	25kg Bag	18.5 kg/m ² per cm of thickness
	Mapegrout T60	Sulphate-resistant thixotropic fibre-reinforced mortar for the repair of concrete. Repairs up to 40 mm thick	25kg Bag	18.5 kg/m ² per cm of thickness
	Mapegrout Thixotropic	Controlled-shrinkage fibre-reinforced grout for the repair of concrete. Repairs up to 30-35 mm thick	25kg Bag	19 kg/m ² per cm of thickness
	Mapegrout Gunite	Single-component premixed non-accelerated cementitious grout for use as dry mix shotcrete.	25kg Bag	20 kg/m ² per cm of thickness
	Mapegrout Hi-Flow	Controlled-shrinkage fibre-reinforced fluid grout for concrete repair.	25kg Bag	20 kg/m ² per cm of thickness

Bonding & Curing Aids



A range of bonding agents and primers to complement both cementitious and epoxy based materials, along with curing agents to assist in controlled hydration.



Manufacturer	Product	Description	Pack Size	Yield
	Nitobond HAR	Nitobond HAR is a recommended primer for the Renderoc cementitious repair systems.	5 / 25 litres	4-6m ² /litre as Primer
	Nitobond AR	Nitobond AR is a primer & Curing Membrane for Renderoc cementitious repair systems.	5 / 25 Litres	4-6m ² /litre as Primer 6-8m ² /litre as Curing Membrane
	Nitobond EP	Epoxy-resin concrete bonding agent	2.5kg Bag	5m ² per bag
	Febond SBR	A styrene-butadiene co-polymer latex specifically designed for use with cementitious mixes.	5 / 25 / 205 Litres	1 Litre per 3m ²
	Eporip	Two-component epoxy material for bonding new to old concrete and for sealing of cracks in screeds	2 / 10kg Bag	0.5-2 kg/m ²
	Eporip Turbo	Two component polyester resin for sealing cracks in screeds and for small reparations.	508g Tub / Tube	Component A = 500g Component B = 8g
	Planicrete	Synthetic-rubber latex additive for interior and exterior cement mixes, to improve mechanical and adhesive characteristics	20 / 5kg Drums	Coverage depends on mortar mix and thickness
	Sikadur 31	Sikadur®-31 Normal is a solvent-free, moisture tolerant, thixotropic, structural two part adhesive and repair mortar, based on epoxy resins and special fillers.	6 kg (Part A+ Part B) Pre batched.	1.55kg/m ² @ 1.0mm thickness, 7.75kg/m ² @ 5.0mm thickness