





Fast Setting Reinstatement Mortar

A range of rapid setting reinstatement and patching mortars to provide hard wearing and durable repairs warehouse floors and loading bays, highways and pavements for both vehicular and pedestrian traffic, some with a temperature range of -20 degrees centigrade.

Manufacturer	Product	Description	Pack Size	Yield
	Patchroc GP	Fast-setting emergency patching mortar for concrete pavements and floors	25kg Bag	12.0 litres / 25 kg bag (1.0 m ² at 12 mm thickness)
	Paveroc	Reinstatement mortar for concrete pavements and floors for the reinstatement of large areas of concrete pavements and floors to avoid the total replacement of bays.	25kg Bag	25 kg yields approx 11.5 litres (0.9 m ² at 12 mm thickness).
	Fosroc XR45	Rapid Setting Cementitious Bedding Mortar	25kg Bag	Approx 12.0 litres / 25 kg bag (1.0 m ² at 12 mm thickness).
	Fosroc XR90	General purpose fast-setting cementitious bedding and repair mortar.	25kg Bag	Approx 12.0 litres / 25 kg bag (1.0 m ² at 12 mm thickness).
	Fosroc XR PE 20	Polyester Resin Mortar for bedding road ironwork where heavily trafficked	15kg Tub	15kg yields approx 7 Litres
	Fosroc RSC	Rapid setting concrete	25kg Bag	25kg yields approx 12.5 Litres
	Fosroc XR Cobbleset	High flow, shrinkage compensated rapid setting grout	25kg Bag	25kg yields approx 13 Litres
	Febset 45	Pre-Mixed Magnesia-Phosphate Cement Mortar, For Rapid, High Early Strength Repair	25kg Bag	25kg combined with the correct amount of water will yield approximately 11.6 ltrs
	Febguard Rapid Repair Mortar	FEBGUARD RAPID REPAIR MORTAR provides preblended material for concrete repair, which reaches an adequate strength for trafficking (or other use) within 90 minutes at 15°C to 20°C	20kg	20kg combined with the correct amount of water will yield approximately 9 ltrs
	Adopatch	A cementitious powder compound with the inclusion of a polymer to promote adhesion and resistance to the passage of water, and a water reducing agent to facilitate a low water cement ratio.	8 / 25kg tub	1Kg fills approx. 0.5 litres
	Mapegrout Fastset	Controlled-shrinkage, fibre-reinforced mortar, with rapid setting and hardening for the repair of concrete, such as balconies, beam edges and columns.	25 kg	18 kg/m ² per 10mm of thickness

