


Corrosion Control Systems




A range of corrosion control systems for a wide range of applications





Manufacturer	Product	Description	Pack Size	Yield
	Galvashield CC	Embedded Sacrificial Anodes for Corrosion Control in Reinforced Concrete	20 Units	N/A
	Galvashield CC Bedding Mortar	Pre-bagged, shrinkage compensated cementitious mortar for drilled in sacrificial anodes	5kg Bag	Sufficient for between 10-20 CC units dependant on unit size
	Ebonex	Discrete Cathodic Protection Anodes for Reinforced Concrete Structures and Steel Framed Buildings	20 Units	N/A
	Ebonex Grout	Pre-bagged, non-shrink cementitious grout for discrete anode anchoring	10kg Bag	6.5 litres/10kg bag
	Galvashield XP	Tied-on sacrificial anode units for corrosion prevention	20 Units	N/A
	Galvashield LJ	Galvanic Cathodic Protection for Reinforced Concrete and Steel Piles in Seawater	Each	N/A

Crack Repairs

A range of thixotropic and low viscosity pourable or injectable crack repair products for repairing cracks from hairline to 10mm wide.

Manufacturer	Product	Description	Pack Size	Yield
	Nitofil LV	Nitofil LV is a two pack low viscosity epoxy resin product for the repair of cracked concrete and masonry by the injection process.	3 Litre Pack	N/A
	Nitofil TH	Is a two pack thixotropic epoxy resin product for the repair of cracked concrete and masonry by the injection process.	1 Litre Pack	N/A
	Epojet	Superfluid epoxy resin for injection. Epojet is used for monolithic repair of structures which have cracked due to overloading or impact.	4 kg (A+B) 2.5 kg (A+B)	sealing of cracks: 1.1 kg/litre bonding concrete-steel: 1.1 kg/m ² per mm of thickness
	Epojet LV	Two component low viscosity epoxy resin for injection. Epojet LV is used for bonding and structural strengthening of concrete and masonry elements by low pressure / atmosphere pressure injection.	5 kg (A+B) 2.5 kg (A+B)	sealing of cracks: 1.1 kg/litre bonding concrete-steel: 1.1 kg/m ² per mm of thickness
	Epo-Crackseal	Epoxy resin crack repair bonder. Penetrating, low viscosity, free flowing epoxy fluid, with excellent bond to damp and dry concrete	2 / 10kg tin	1 litre per Kg

Cleaning & Solvents

Manufacturer	Product	Description	Pack Size	
	Resoklens	Developed for cleaning unhardened epoxy and polyester based materials from tools and surfaces.	5 / 25 Litres	
	Styroklen	Developed to safely dissolve away and emulsify unwanted polystyrene, Bolt boxes or void formers	5 / 25 Litres	
	Adowash	High efficiency white spirit solvent for cleaning spirit based product from sprayers, tools and surfaces.	5 / 25 Litres	