





Screeding

Manufacturer	Product	Description	Pack Size	Yield
 BASF The Chemical Company	Febscreed	FEBSCREED is a polymer modified shrinkage compensated, cementitious, self levelling floor screed in powder form requiring only the addition of water	25kg Bag	1.8 – 2.0 kg per m ² per mm thickness, depending on surface.
	Febond SBR	FEBOND SBR is a styrene-butadiene co-polymer latex specifically designed for use with cementitious mixes.	5 / 25 / 205 Litres	1 litre of FEBOND SBR will typically produce enough slurry to coat 3 square metres
 MAPEI	Topcem	Normal setting special hydraulic binder with rapid drying (4-7 days).	20kg Bag	2-2.5 kg/m ² per cm of thickness
	Topcem Pronto	Ready to use, pre-blended, normal-setting mortar with controlled shrinkage for fast-drying screeds (4 days).	25kg Bag	18-20 kg/m ² per cm of thickness, depending on tamping
	Eporip	Two-component epoxy material for bonding new to old concrete and for sealing of cracks in screeds	2 / 10kg Bag	0.5-2 kg/m ²
	Mapecem	Special fast setting hydraulic binder for the preparation of fast-drying screeds with controlled shrinkage	20kg Bag	3.5-4.5 kg/m ² per 10mm of thickness
	Planicrete	Synthetic-rubber latex additive for interior and exterior cement mixes, to improve mechanical and adhesive characteristics	20 / 10 / 5kg Drums	Coverage depends on mortar mix and thickness



Dry Shake Topping Systems

Manufacturer	Product	Description	Pack Size	Yield
 DCP	Tibmix	Tibmix is a pre-blended mix of specially graded Betonac aggregate and OPC designed to be applied to freshly laid concrete floors to substantially increase the durability of the base concrete.	25kg	5.4kg / m ²
	Tibmix Pigmented	As Tibmix above but available in a range of colours	25kg	5.4kg / m ²
	Monoshake	Monoshake is a pre-blended mix of specially graded Quartz aggregates, OPC and special additives designed to be applied to freshly laid concrete floors to combine with the slab and create a monolithic surface. Primarily used as a dry shake topping in a wide range of industrial applications.	25kg	3 - 5kg / m ²
	Monoshake Pigmented	As Tibmix above but available in a range of colours	25kg	3 - 5kg / m ²
 FOSROC	Nitoflor Hardtop S	A dry shake floor hardener for new concrete floors	25 kg	5kg/m ²