





## Floor Joint Sealants



Manufacturer	Product	Description	Pack Size	Yield
	Nitoseal MS300	Nitoseal MS300 is suitable for sealing saw-cut and movement joints in internal floors, and external joints where abrasion resistance is required.	600 ml sachets. (10 no. per box)	Dependant upon joint size
	Nitoseal MS600	Nitoseal MS600 is suitable for sealing movement joints in buildings and civil engineering structures including joints that will be subject to intermittent or permanent immersion.	600 ml sachets. (10 no. per box)	Dependant upon joint size
	Colpor 200PF	For the sealing and maintenance of joints in concrete roads, concrete runways and hard standings. Colpor 200PF is particularly suitable for sealing areas where fuel and oil spillage might occur.	2 x 5 litre units, (5L of base & 5L of curing agent.)	Dependant upon joint size
	Thioflex 1	Thioflex One is a one part polysulfide joint sealant which, on exposure to atmospheric moisture, cures to form a flexible rubber seal.	380ml Cartridge	Dependant upon joint size
	Thioflex 600	Thioflex 600 is available in gun and pouring grades. The gun grade is ideal for general application. It is packed in a ready to mix, 2.5 litre tin containing the base and curing agent in the correct proportions	2.5 / 5 Litres	Dependant upon joint size
	Nitoseal MS50	Nitoseal MS50 is suitable for sealing joints in Concrete, Brickwork, Blockwork, Perimeter sealing around doors and windows, Non-trafficked floor joints.	600ml sachets (10 per box in grey) 380ml cartridges (20 per box in colours)	Dependant upon joint size
	Plastic N2	Hot-poured rubber bitumen horizontal joint sealant for sealing movement and construction joints in pavements, floor slabs, water retaining and water excluding structures.	15kg Bag	Dependant upon joint size

## Epoxy Floor Paint

Manufacturer	Product	Description	Pack Size	Yield
 	Mapecoat I24	Epoxy paint for acid-resistant non-toxic coating of concrete surfaces.	5 kg (4kg A+1kg B).	400-600 g/m2 per coat depending on the type of substrate
		<p>Mapecoat I24 is used to coat concrete surfaces designed for contact with food products e.g. wine, oil, confectionery industries.</p> <p>Mapecoat I24 is especially recommended for coating reservoirs built to contain drinking water.</p>		