



## Expanding & Plasticising Grout Admixtures





Plasticising admixtures for site mix concrete allowing the use of less water, producing an expansion medium with consequent strength and



| Manufacturer  | Product   | Description   | Pack Size       | Yield  |
|---|-----------|---|-----------------|--|
|  | Cebex 100 | Plasticised expanding grout admixture   | 24 x 225g Packs | (225g + 22L Water + 50kg OPC) yields 36 Litres |
|   | AdogROUT  | Pourable grade used where hole is 8 to 40mm greater in diameter than the bar. | 227g            | N/A  |



## Repair Compounds - Resin Based

A range of two and three component epoxy resin based repair compounds, providing high strength gain and chemical resistance. Available in a range of product for repairing loading bays, airport aprons, sea walls, warehousing and acid tanks etc.

| Manufacturer  | Product        | Description   | Pack Size  | Yield  |
|---|----------------|---|--|--|
|   | Nitomortar S   | High strength, abrasion-resistant epoxy reinstatement mortar  | 5 / 16kg   | 2.5 litres / 5 kg 'Standard' pack<br>8.0 litres / 16 kg 'Industrial' |
|   | Nitomortar HB  | High build epoxy reinstatement mortar   | 2.9 / 9.3 kg   | 2.5 litres / 2.9 kg 'Standard'<br>8.0 litres / 9.3 kg 'Industrial'   |
|   | Nitomortar FC  | Epoxy resin fairing coat  | 1kg Bag  | 1 kg pack = 0.6 ltr  |
|   | Febset NF      | High Strength Non-Flow Epoxy Bedding and Repair Mortar  | 3kg tin  | 3kg covers 1.1m <sup>2</sup> at 1.5mm thickness                      |
|   | Febplate       | High Performance Epoxy Resin Repair Compound And Bedding Mortar   | 20 kg  | 20 Kg covers 2 m <sup>2</sup> at 5mm thickness                       |
|   | Planigrout 300 | Fluid three-component epoxy mortar for the repair of damaged concrete structures, precision fastening and reinforcement of industrial flooring. | 12.2kg Bag (Part A - 1.6kg)<br>(Part B - 0.6kg)<br>(Part C - 10kg) | 2 kg/m <sup>2</sup> per mm of thickness                              |
|  | Quickmast 201  | QUICKMAST 201 is a three component solvent-free, high strength epoxy mortar designed principally for use in construction and renovation work.   | 5 / 15 kg tub  | 5Kg Pack - 2.5 litres<br>15Kg Pack - 7.5 litres                      |
|   | Quickmast 201E | Quickmast 201 E is a high strength epoxy mortar, designed principally for use in construction and renovation work.                              | 23kg tin   | 23kg covers 1.1m <sup>2</sup> at 10mm thickness                      |

## Polyester Resin Mortars

A range polyester resin based repair compounds, providing high strength gain and chemical resistance. Available in a range of product for repairing loading bays, airport aprons, sea walls, warehousing and acid tanks etc.

| Manufacturer  | Product       | Description  | Pack Size        | Yield                                     |
|---|---------------|--|------------------|---|
|  | Nitomortar PE | High strength jointing and multi-purpose repair compounds for fast and emergency reinstatement of concrete, bedding, jointing and reprofiling of concrete, masonry and brickwork.  | 14kg             | 7.5 litres / 14 kg pack                   |
|   | Adesilex PG2  | Adesilex PG2 is a two-component epoxy resin based product with special hardeners, selected fine aggregate and special additives. Recommended for structural strengthening including bonding steel plates to concrete, rigid structural bonding of pre-cast concrete elements and sealing large cracks. | 6 kg (A+B) units | 1.6 kg/m <sup>2</sup> per mm of thickness |