







## Concrete Surface Treatments

Manufacturer	Product	Description	Pack Size	Yield
	Adocure Standard	Resin based curing compound of 75% efficiency. Solution of inert resins in evaporative solvents for use in general construction projects. WBS Listed for drinking water projects	25 / 210 Litres	5.5m <sup>2</sup> / litre
	Adocure Super	Resin based curing compound of 90% efficiency. Similar to Adocure Standard but with a higher curing efficiency. WBS Listed for drinking water projects	25 / 210 Litres	5.5m <sup>2</sup> / litre
	Adocure Super AL	Available aluminised (SUPER AL) for use in strong sunlight conditions and where DTP stipulate aluminised for highways, bridges, runways, etc.	25 / 210 Litres	5.5m <sup>2</sup> / litre
	Safecure Super	A spray-on temporary membrane to retain moisture in freshly placed concrete. Degrades when exposed to ultraviolet light over a period of time. Clean spraying equipment using water.	25 / 210 Litres	5.5m <sup>2</sup> / litre
	Adocure WW	Aqueous silicate solution that reacts to deposit an integral layer of high cohesive strength crystals to provide a permanent membrane. WBS Listed for drinking water projects.	25 / 210 Litres	5.5m <sup>2</sup> / litre
	Adocure WWT	Fugitive Dye Tinted (WWT) form to suit specification and improve visual indication of application.	25 / 210 Litres	5.5m <sup>2</sup> / litre
	Adocure sealer	Combined Curing Agent/Sealer, 75% curing efficiency to ASTM C390. High solids resin based compound to cure and provide a long term seal in one operation	25 / 210 Litres	6.0m <sup>2</sup> / litre
	Adocure sealer PF	A clear acrylic polymer resin solution for application to surfaces of freshly laid concrete floors that have been finished by power floating	25 / 210 Litres	6.0m <sup>2</sup> / litre
	Extraseal AC3	Extraseal AC3 is a specially formulated clear acrylic resin polymer compound designed specifically for the initial curing of freshly placed concrete, combined with the added benefits of sealing, hardening and dustproofing the concrete surfaces.	25 / 210 Litres	6.0m <sup>2</sup> / litre
	Safewallseal	A low odour, VOC compliant, polyurethane acrylic dispersion for sealing bricks, blocks and renders	5 / 25 / 210 Litres	5-8m <sup>2</sup> per litre per coat
	Antipluviol	Silicone water-repellent in water solution for exterior walls.	5 / 25 kg	100-150 g/m <sup>2</sup>




## Concrete Surface Hardening

Manufacturer	Product	Description	Pack Size	Yield
	Adotuf	Spray or brush applied surface hardener and dustproofer for new and existing concrete floors. When applied it will greatly extend the life and durability of the floor and also dustproof old floors.	5 / 25 / 210 Litres	10-12 m <sup>2</sup> / L
	Nitoflor Lithurin	Permanent hardening and dustproofing compound for concrete surfaces. Suitable for use on concrete and granolithic surfaces.	15kg Bag	150- 200m <sup>2</sup>

## Concrete Surface Sealing

Manufacturer	Product	Description	Pack Size	Yield
 	Safewallseal	High Performance Water Based Masonry Sealer, with low odour, VOC compliant, polyurethane acrylic dispersion for sealing bricks, blocks and renders.	5 / 25 / 210 Litres	5 - 8m <sup>2</sup> / litre
	Safefloorseal	High Performance Water Based Concrete Sealer, with low odour, VOC compliant, polyurethane acrylic dispersion for sealing concrete floors which performs equally well on both interior and exterior concrete.	5 / 25 / 210 Litres	5 - 6m <sup>2</sup> / litre
	Safeblockseal	High Performance Water Based Block Paving Sealer, with low odour, VOC compliant, polyurethane acrylic dispersion specifically developed for sealing block paving.	5 / 25 / 210 Litres	5 - 8m <sup>2</sup> / litre
	Resoseal	Urethane resin floor sealer. Seals and bonds concrete floors. Increases resistance to chemical spillage	5 / 25 Litres	5 - 8m <sup>2</sup> / litre

## Smoothing Screeds & Floor Levelling

Manufacturer	Product	Description	Pack Size	Yield
 The Chemical Company	Febflor	FEBFLOR is a cementitious floor levelling and smoothing compound in powder form requiring only the addition of water.	15 / 25kg Bag	1.5-2 Kg per m <sup>2</sup> at a thickness of 1.5 mm depending on surface.
	Febflor +	FEBFLOR PLUS is a polymer modified shrinkage compensated, cementitious floor levelling and smoothing compound in powder form requiring only the addition of water.	25kg Bag	3.6 - 4 Kg per m <sup>2</sup> at a thickness of 2mm depending on surface
	Febflor latex	FEBFLOR LATEX is a two component floor levelling compound comprising a bag of powder and a bottle of polymer latex.	25 Kg units (20 Kg Powder 5 litre bottle)	25kg will cover approx 4 m <sup>2</sup> at a thickness of 3 mm
 	Ultraplan Eco	Water-bored ultra-fast hardening self-levelling compound for thicknesses from 1 to 10 mm per coat.	23kg Bag	1.6 kg/m <sup>2</sup> per mm of thickness
	Ultraplan Maxi	Water-bored ultra-fast hardening self-levelling compound for thicknesses from 3 to 30 mm per coat	25kg Bag	1.6 kg/m <sup>2</sup> per mm of thickness
	Latexplan	Two-part levelling and smoothing compound, consisting of special cements and a syntetic rubber latex. For interior levelling of differences in thickness up to 10 mm	30 Kg units (25 Kg Powder 5 litre bottle)	6 m <sup>2</sup> at 3 mm thickness